Wallpaper Symbols and Their Meanings

WATER-RESISTANT
Fresh paste marks can be dabbed off with a damp sponge.



WASHABLE
Light stains can be removed with a damp sponge.



EXTRA WASHABLE
Stains, except for oil, grease and similar substances, can be removed using a mild soapy solution and a sponge.



SCRUBBABLE
Water-soluble stains can be removed using a mild soapy solution or a mild abrasive cleaner and a sponge or soft brush.



EXTRA SCRUBBABLE
Heavier water-soluble stains can be removed by wet cleaning with a sponge or soft brush.



ADEQUATE LIGHTFASTNESS
Limited resistance to exposure to light.



GOOD LIGHTFASTNESS
Good resistance to normal exposure to light.



FREE MATCH
No pattern matching is required when hanging the wallpaper.



STRAIGHT MATCH
Identical pattern elements must be aligned at the same height on adjacent strips.



OFFSET MATCH
The pattern on each subsequent strip is shifted by the specified offset.



REVERSAL OF ALTERNATE LENGTHS
Every second length of wallpaper must be hung upside down.



PASTE THE WALLPAPER
The paste must be applied to the back of the wallpaper.



PASTE THE WALL
The paste must be applied directly to the wall or substrate.



PEELABLE
When redecorating, the top layer of the wallpaper can be peeled off dry. The backing layer remains on the wall and can serve as lining paper.

Erismann & Cie. GmbH, Tapetenfabrik, Hafenstraße 19, 79206 Breisach, Germany
Telefon +49 7667 909-0, Fax +49 7667 909-220, info@erismann.de



WET REMOVABLE
The wallpaper must be thoroughly soaked with water and removed using a scraper.



DRY STRIPPABLE
When redecorating, the wallpaper can be completely removed from the wall while dry without leaving any residue.



DUPLEX EMBOSSED WALLCOVERING
A high-quality embossed wallcovering made from two laminated layers of paper. The embossing remains stable during installation.



DOUBLE-CUT SEAM
For heavy wallcoverings that do not require pattern matching. Each new length overlaps the previous one by approximately 5–8 cm. In the overlapping area, both lengths are cut vertically freehand using a special wallcovering seam cutter.



PRE-PASTED WALLPAPER
The back of the wallpaper is pre-coated with paste, which is activated by briefly soaking it in water.

Erismann & Cie. GmbH, Tapetenfabrik, Hafenstraße 19, 79206 Breisach, Germany
Telefon +49 7667 909-0, Fax +49 7667 909-220, info@erismann.de